

## TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor  
 Description: RT 857 is a road-oriented tire for haulage operations as well as for soil tillage and vineyard harvesting applications. Its strong casing along with polyester belts offers excellent driving comfort and puncture resistance. Its stubble-resistant tread compound features high cut and chip resistance.

**Pattern Name**      **RT 857**  
 Version: STANDARD  
 US Code: 94041923  
 Type: TL  
 Tire Size: 320/85 R 28  
 LI/SS: 124 A8/B



Dimensions (U/M US Standard)  
 Section Width (in): 13.0  
 Overall Diameter (in): 49.4  
 Static Loaded Radius (in): 22.7  
 Rolling Circumference (in): 148.8  
 SRI: 600  
 Rim Rec: W 11  
 Rim Alt: W 9 ; W 10  
 ECE: E4-106R-000757

### LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23
30	1940	2260	2580	2900	3220	3530
25	1940	2260	2580	2900	3220	3530
20	2080	2420	2770	3110	3450	3780
5 LT	2600	3030	3460	3880	4310	4730
5 HT	2080	2420	2770	3110	3450	3780