

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor
 Description: AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name AGRIMAX RT 657

Version: STANDARD
 Type: TL
 Tire Size: 340/65 R 20
 LI/SS: 124 D/127 A8



Dimensions (U/M International standard)

Section Width (mm): 343
 Overall Diameter (mm): 950
 Static Loaded Radius (mm): 430
 Rolling Circumference (mm): 2892
 SRI: 450
 Rim Rec: W 11
 Rim Alt: W 10 ; W 12

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	755	880	1010	1120	1235	1330	1475	1600
50	790	925	1060	1180	1295	1395	1550	1680
40	825	965	1105	1225	1350	1455	1610	1750
30	865	1015	1160	1290	1420	1530	1695	1840
10 LT	1010	1180	1355	1505	1655	1785	1975	2145
10 HT	865	1015	1160	1290	1420	1530	1695	1840