

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD

Type TL

Tire Size 320/65 R 16

LI/SS 117 D/120 A8



Dimensions (U/M International standard)

Section Width (mm) 319

Overall Diameter (mm) 822

Static Loaded Radius (mm) 366

Rolling Circumference (mm) 2466

SRI 390

Rim Rec W 10

Rim Alt W 9 ; W 11

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	605	710	810	900	990	1070	1185	1285
50	635	745	855	945	1040	1125	1245	1350
40	660	770	885	980	1080	1165	1290	1400
30	700	815	935	1040	1140	1230	1365	1480
10 LT	815	950	1090	1210	1330	1435	1590	1725
10 HT	700	815	935	1040	1140	1230	1365	1480