

TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader
 Description: FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

Pattern Name **FL 630 SUPER**

Version: STANDARD
 US Code: 94042135
 Type: TL
 Tire Size: 750/60 R 26.5
 LI/SS: 180 D



Dimensions (U/M US Standard)
 Section Width (in): 29.7
 Overall Diameter (in): 62.0
 Static Loaded Radius (in): 27.3
 Rolling Circumference (in): 189
 SRI: 725
 Rim Rec: AG 24.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	5160	5960	6770	8210	9500	10950	12400	13360	14810	16090
40	5640	6530	7410	8990	10410	11990	13580	14640	16230	17640
30	6830	7900	8970	10890	12600	14520	16430	17710	19640	21340
25	7680	8880	10070	12230	14150	16310	18470	19920	22070	23980
15	8920	10320	11710	14220	16450	18960	21460	23140	25640	27860
5	10160	11750	13340	16190	18740	21590	24450	26350	29210	31740