

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader
 Description FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

Pattern Name FL 630 SUPER

Version STANDARD
 US Code 94042166
 Type TL
 Tire Size 560/60 R 22.5
 LI/SS 161 D



Dimensions (U/M US Standard)
 Section Width (in) 21.4
 Overall Diameter (in) 49.0
 Static Loaded Radius (in) 21.6
 Rolling Circumference (in) 149
 SRI 600
 Rim Rec AG 16.00
 Rim Alt 17.00 ; 20.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	3000	3470	3940	4680	5530	6330	7030	7870	8620	9370
40	3260	3780	4290	5100	6020	6890	7650	8560	9380	10200
30	3960	4570	5190	6170	7290	8330	9260	10370	11360	12350
25	4440	5140	5830	6930	8190	9370	10410	11650	12760	13870
15	5160	5970	6780	8060	9510	10880	12090	13550	14840	16110
5	5870	6800	7720	9180	10840	12390	13770	15420	16890	18350