

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: STANDARD
 US Code: 94042531
 Type: TL
 Tire Size: 210/90 R 24
 LI/SS: 107 A8/B



Dimensions (U/M US Standard)
 Section Width (in): 8.4
 Overall Diameter (in): 39.8
 Static Loaded Radius (in): 18.2
 Rolling Circumference (in): 119.2
 SRI: 475
 Rim Rec: W 7
 Rim Alt: W 6

LOAD CAPACITY TABLE (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 |
|-----------|------|------|------|------|------|------|------|------|------|
| 30 | 1010 | 1170 | 1330 | 1510 | 1690 | 1850 | 2010 | 2150 | - |
| 25 | 1010 | 1170 | 1330 | 1510 | 1690 | 1850 | 2010 | 2150 | - |
| 20 | 1090 | 1250 | 1430 | 1620 | 1810 | 1980 | 2150 | 2300 | - |
| 5 | 1490 | 1720 | 1910 | 2110 | 2330 | 2560 | 2980 | 3140 | 3230 |