

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: STANDARD
 US Code: 94042548
 Type: TL
 Tire Size: 210/95 R 28
 LI/SS: 116 A8/B



Dimensions (U/M US Standard)
 Section Width (in): 8.4
 Overall Diameter (in): 43.7
 Static Loaded Radius (in): 20.2
 Rolling Circumference (in): 131.2
 SRI: 550
 Rim Rec: W 7
 Rim Alt: W 6

LOAD CAPACITY TABLE (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 |
|-----------|------|------|------|------|------|------|------|------|------|
| 30 | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 | - |
| 25 | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 | - |
| 20 | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 | - |
| 5 | 1910 | 2190 | 2450 | 2690 | 2980 | 3270 | 3800 | 4010 | 4130 |