

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
 US Code 94042753
 Type TL
 Tire Size 440/65 R 20
 LI/SS 138 D/141 A8

Dimensions (U/M US Standard)

Section Width (in) 17.4
 Overall Diameter (in) 42.5
 Static Loaded Radius (in) 18.9
 Rolling Circumference (in) 127.6
 SRI 525
 Rim Rec W 14 L
 Rim Alt W 13 ; W 15 L
 ECE E4-106R-000760



LOAD CAPACITY TABLE (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 2450 | 2870 | 3280 | 3650 | 4010 | 4320 | 4790 | 5200 |
| 30 | 2580 | 3010 | 3450 | 3840 | 4210 | 4540 | 5040 | 5470 |
| 25 | 2680 | 3130 | 3580 | 3980 | 4380 | 4720 | 5220 | 5680 |
| 20 | 2820 | 3300 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |
| 5 LT | 3280 | 3850 | 4400 | 4890 | 5380 | 5800 | 6430 | 6980 |
| 5 HT | 2820 | 3300 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |