

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader

Description RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

Pattern Name **RIDEMAX FL 693 M**

Version STANDARD
US Code 94043019
Type TL
Tire Size 650/50 R 22.5
LI/SS 163 D/160 E



Dimensions (U/M US Standard)

Section Width (in) 25.4
Overall Diameter (in) 48.1
Static Loaded Radius (in) 21.1
Rolling Circumference (in) 146.3
SRI 575
Rim Rec AG 20.00

LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3630	4070	5060	5750	6650	7540	8230	9030	9920
40	3920	4410	5490	6240	7210	8170	8930	9790	10750
30	4750	5330	6640	7550	8720	9890	10800	11840	13010
25	5350	6000	7460	8490	9800	11110	12140	13300	14620
15	6210	6970	8660	9850	11390	12920	14110	15460	16990
5	7070	7940	9880	11220	12960	14700	16060	17610	19340