

TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader

Description: RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

Pattern Name **RIDEMAX FL 693 M**

Version: STANDARD
 US Code: 94043767
 Type: TL
 Tire Size: 500/45 R 22.5
 LI/SS: 146 D/143 E



Dimensions (U/M US Standard)

Section Width (in): 19.8
 Overall Diameter (in): 40.2
 Static Loaded Radius (in): 17.9
 Rolling Circumference (in): 122.6
 SRI: 500
 Rim Rec: AG 16.00

LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	2200	2470	3060	3490	4030	4570	4990	5470	6010
40	2410	2710	3370	3840	4430	5030	5490	6020	6610
30	2930	3280	4090	4650	5370	6080	6650	7290	8000
25	3300	3690	4600	5220	6030	6840	7470	8190	8990
15	3820	4290	5330	6060	7010	7950	8670	9510	10450
5	4350	4880	6070	6910	7980	9050	9890	10840	11900