

## TECHNICAL SPECIFICATION

Applications                      Spreader / Harvester  
 Description                      Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

**Pattern Name                      AGRIMAX TERIS**

Version                              STANDARD  
 US Code                            94044634  
 Type                                 TL  
 Tire Size                          520/85 R 42  
 LI/SS                                168 D



Dimensions (U/M US Standard)  
 Section Width (in)              20.3  
 Overall Diameter (in)          76.8  
 Static Loaded Radius (in)      35.0  
 Rolling Circumference (in)    230.4  
 SRI                                  925  
 Rim Rec                          DW 16 L  
 Rim Alt                              DD 18 L

**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23	29	35	41	46	55
40	4080	4820	5560	6170	6920	7540	8770	10010	11240	12350	-
30	4290	5060	5840	6480	7260	7910	9200	10500	11810	12960	-
25	4460	5280	6100	6770	7580	8260	9610	10960	12310	13520	-
20	4700	5540	6390	7100	7960	8660	10090	11510	12930	14200	-
15	4840	5710	6590	7320	8200	8940	10390	11860	13330	14640	-
5	6120	7230	8330	9260	10370	11300	13150	15000	16850	18520	-
5 Cyc.	-	-	-	-	-	-	-	-	-	-	20990