

## TECHNICAL SPECIFICATION

Applications: Spreader / Harvester  
 Description: Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

**Pattern Name      AGRIMAX TERIS**

Version: STANDARD  
 US Code: 94044641  
 Type: TL  
 Tire Size: IF 580/80 R 34 CFO  
 LI/SS: 177 D



Dimensions (U/M US Standard)

Section Width (in): 23.1  
 Overall Diameter (in): 70.6  
 Static Loaded Radius (in): 31.9  
 Rolling Circumference (in): 212.2  
 SRI: 850  
 Rim Rec: DW 20 B ; DW 20 A  
 Rim Alt: DW 21 A ; DW 21 B

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52
40	5960	6920	7890	9020	9990	10950	11920	12720	14010	15130	16090
30	5960	6920	7890	9020	9990	10950	11920	12720	14010	15130	16090
25	5960	6920	7890	9020	9990	10950	11920	12720	14010	15130	16090
20	5960	6920	7890	9020	9990	10950	11920	12720	14010	15130	16090
20 Cyc.	7750	8990	10260	11720	12980	14230	15490	16530	18210	19680	20920
15	5960	6920	7890	9020	9990	10950	11920	12720	14010	15130	16090
10 Cyc.	9250	10720	12230	13980	15480	16960	18470	19720	21710	23460	24940
5	5960	6920	7890	9020	9990	10950	11920	12720	14010	15130	16090