

## TECHNICAL SPECIFICATION

Applications: Trailer / Implement Machinery / Hay Harvester / Baler  
 Description: AW 711 is an implement radial tire specially designed for modern farming, and suitable for general purpose applications. Thanks to its special tread compound, the AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption.

**Pattern Name**      **AW 711**  
 Version: STUBBLE RESISTANT  
 US Code: 94044757  
 Type: TL  
 Tire Size: 380/55 R 16.5  
 LI/SS: 150 A8/B



Dimensions (U/M US Standard)  
 Section Width (in): 14.2  
 Overall Diameter (in): 32.7  
 Static Loaded Radius (in): 14.6  
 Rolling Circumference (in): 98.4  
 SRI: 390  
 Rim Rec: 12  
 Rim Alt: 11.75  
 ECE: E4-106R-001393

**LOAD CAPACITY TABLE (lbs)**

mph / psi	12	17	23	29	35	41	46	52	58	73
30	2220	2890	3550	4070	4730	5400	5760	6360	6940	7400
25	2220	2890	3550	4070	4730	5400	5760	6360	6940	7400
20	2490	3230	3980	4560	5300	6050	6460	7120	7780	8280
15	2650	3440	4230	4840	5630	6430	6870	7570	8280	8800
10	2800	3640	4480	5130	5960	6800	7270	8010	8760	9310
5	3110	4030	4970	5690	6620	7550	8070	8900	9720	10340