

**TECHNICAL SPECIFICATION**

Applications                      Trailer / Compact Utility Tractor  
 Description                      BK 308 has been specially designed for trailers and utility tractors. It features excellent traction on all surfaces and tread tie bars to reduce tread groove cracking. The strong casing provides excellent durability and puncture resistance whereas the special tread compound ensures a longer service life.

**Pattern Name                      BK 308**

Version                              STANDARD  
 US Code                            94044993  
 Type                                 TT  
 Tire Size                          6.50 - 20  
 LI/SS                               104 A8  
 PR                                    10



Dimensions (U/M US Standard)  
 Section Width (in)              7.5  
 Overall Diameter (in)          34.1  
 Rim Rec                            5.50 F  
 Rim Alt                              4.00 E ; 5.00 F

**LOAD CAPACITY TABLE (lbs)**

mph / psi	70
25	1985

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.  
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..