

## TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor  
 Description: RT 857 is a road-oriented tire for haulage operations as well as for soil tillage and vineyard harvesting applications. Its strong casing along with polyester belts offers excellent driving comfort and puncture resistance. Its stubble-resistant tread compound features high cut and chip resistance.

**Pattern Name RT 857**

Version: STANDARD  
 US Code: 94045013  
 Type: TL  
 Tire Size: 420/85 R 26  
 LI/SS: 138 A8/B



Dimensions (U/M US Standard)  
 Section Width (in): 17.2  
 Overall Diameter (in): 54.1  
 Static Loaded Radius (in): 24.3  
 Rolling Circumference (in): 162  
 SRI: 650  
 Rim Rec: DW 15 L  
 Rim Alt: W 14 L ; W 15 L ; W 16 L ; DW 16 L  
 ECE: E11-106R-003471  
 TRA Code: R-1

**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23
30	2870	3340	3800	4280	4740	5200
25	2870	3340	3800	4280	4740	5200
20	3080	3570	4080	4570	5080	5580
5 LT	3850	4480	5100	5730	6360	6980
5 HT	3080	3570	4080	4570	5080	5580