

## TECHNICAL SPECIFICATION

Applications                      Trailer / Tanker / Spreader  
 Description                      FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

**Pattern Name                      FL 630 SUPER**

Version                              STANDARD  
 US Code                            94045037  
 Type                                 TL  
 Tire Size                          580/65 R 22.5  
 LI/SS                                166 D



Dimensions (U/M US Standard)

Section Width (in)              22.7  
 Overall Diameter (in)          52.2  
 Static Loaded Radius (in)      23.4  
 Rolling Circumference (in)    159.8  
 SRI                                  625  
 Rim Rec                            AG 18.00  
 Rim Alt                             AG 16.00 ; AG 17.00 ; AG 20.00

LOAD CAPACITY TABLE (lbs)

| mph / psi | 12   | 15   | 17   | 23    | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 3440 | 3980 | 4520 | 5380  | 6350  | 7260  | 8070  | 9030  | 9890  | 10750 |
| 40        | 3750 | 4330 | 4920 | 5840  | 6900  | 7890  | 8760  | 9820  | 10760 | 11680 |
| 30        | 4530 | 5240 | 5940 | 7080  | 8340  | 9560  | 10610 | 11880 | 13020 | 14140 |
| 25        | 5090 | 5890 | 6680 | 7950  | 9380  | 10740 | 11930 | 13360 | 14630 | 15890 |
| 15        | 5910 | 6830 | 7760 | 9240  | 10900 | 12470 | 13860 | 15510 | 16990 | 18460 |
| 5         | 6730 | 7790 | 8840 | 10520 | 12410 | 14200 | 15770 | 17670 | 19360 | 21030 |