

TECHNICAL SPECIFICATION

Applications High Power Tractor

Description AGRIMAX FORCE, the high-end product of BKT, is a radial tire specially designed for agriculture applications with high-power tractors, ensuring top performance and efficiency. AGRIMAX FORCE is a really comfortable tire for both field operations and road transfers; it actually allows to move without the need for increasing the inflation pressure.

Pattern Name **AGRIMAX FORCE**

Version STANDARD

US Code 94045228

Type TL

Tire Size IF 600/70 R 34

LI/SS 167 D



Dimensions (U/M US Standard)

Section Width (in) 23.7

Overall Diameter (in) 67.1

Static Loaded Radius (in) 29.8

Rolling Circumference (in) 199.6

SRI 800

Rim Rec DW 21 B ; DW 21 A

Rim Alt DW 20 A ; DW 20 B

ECE E4-106R-001408

LOAD CAPACITY TABLE (lbs)

mph / psi*	9	12	15	17	20	23	29	35
45	5130	5900	6770	7650	8520	9390	10260	10920
from 40 to 25	5640	6480	7440	8410	9370	10330	11290	12000
20	5860	6730	7740	8740	9740	10740	11730	12490
12	6080	7000	8040	9080	10120	11140	12180	12970
5	7160	8220	9450	10680	11890	13110	14330	15260
5 Cyc*	7890	9070	10420	11770	13120	14450	15800	16820
5 HT	5860	6730	7740	8740	9740	10740	11730	12490

* - For 10 Cyc application inflation pressure to be increased by 0.8 bar.