

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name AGRIMAX RT 855

Version: STEEL BELTED
 US Code: 94045358
 Type: TL
 Tire Size: 480/80 R 50
 LI/SS: 176 A8



Dimensions (U/M US Standard)

Section Width (in): 19.3
 Overall Diameter (in): 80.2
 Static Loaded Radius (in): 37.2
 Rolling Circumference (in): 245.2
 SRI: 975
 Rim Rec: DW 16 A
 Rim Alt: DW 15 A ; W 15 A

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52	58	64	73
30	4540	5210	5990	6760	7530	8300	8970	9640	10490	11430	12060	12840	13930	15650
25	4540	5210	5990	6760	7530	8300	8970	9640	10490	11430	12060	12840	13930	15650
20	4860	5580	6400	7230	8060	8880	9610	10330	11230	12230	12910	13750	14910	16750
5 LT	6080	6990	8020	9060	10090	11120	12030	12930	14060	15320	16160	17210	18670	20980
5 HT	4860	5580	6400	7230	8060	8880	9610	10330	11230	12230	12910	13750	14910	16750