

## TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader  
 Description: FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

**Pattern Name**      **FL 630 SUPER**

Version: STANDARD  
 US Code: 94045587  
 Type: TL  
 Tire Size: 650/65 R 26.5  
 LI/SS: 174 D



Dimensions (U/M US Standard)  
 Section Width (in): 25.4  
 Overall Diameter (in): 59.8  
 Static Loaded Radius (in): 26.9  
 Rolling Circumference (in): 183.2  
 SRI: 725  
 Rim Rec: AG 20.00

**LOAD CAPACITY TABLE (lbs)**

mph / psi	12	15	17	23	29	35	41	46	52	58
45	4310	4980	5650	6870	7940	9150	10360	11170	12380	13450
40	4730	5470	6210	7540	8720	10050	11380	12270	13590	14770
30	5730	6620	7520	9130	10550	12160	13770	14850	16460	17880
25	6440	7440	8440	10250	11860	13670	15480	16690	18500	20090
15	7470	8640	9810	11920	13780	15880	17980	19380	21480	23350
5	8510	9840	11180	13570	15700	18090	20480	22070	24470	26590