

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader
 Description FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

Pattern Name FL 630 SUPER

Version STANDARD
 US Code 94045594
 Type TL
 Tire Size 650/65 R 30.5
 LI/SS 176 D



Dimensions (U/M US Standard)
 Section Width (in) 25.4
 Overall Diameter (in) 63.8
 Static Loaded Radius (in) 28.9
 Rolling Circumference (in) 195.9
 SRI 775
 Rim Rec AG 20.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	4560	5280	6000	7270	8410	9700	10980	11840	13120	14250
40	5020	5800	6580	7990	9240	10650	12060	13000	14410	15650
30	6070	7020	7960	9670	11190	12890	14590	15730	17440	18950
25	6820	7890	8950	10870	12570	14480	16400	17680	19600	21300
15	7930	9160	10390	12620	14590	16820	19050	20530	22760	24730
5	9020	10430	11840	14370	16630	19170	21700	23390	25920	28170