

TECHNICAL SPECIFICATION

Applications Tractor
Description TRAC FARM PLUS is a rear tractor tire specifically designed for farming applications. The tire features a deeper tread with dual angle lugs and extra rubber at the center to ensure both excellent traction and a comfortable ride on the road. The special tread design provides more contact for better stability whereas the strong casing offers excellent resistance against stub penetration. TRAC FARM PLUS is made of a superior tread compound optimizing wear and tear resistance and ensuring a longer tire life-cycle.

Pattern Name TRAC FARM PLUS

Version STANDARD
US Code 94045686
Type TT
Tire Size 13.6 - 28
LI/SS 124 A8
PR 12



Dimensions (U/M US Standard)
Section Width (in) 14.4
Overall Diameter (in) 53.0
Static Loaded Radius (in) 24.4
Rolling Circumference (in) 160.9
Rim Rec W 12
Rim Alt W 11

LOAD CAPACITY TABLE (lbs)

mph / psi	34
25	3530

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..