

## TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader

Description: RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

**Pattern Name**      **RIDEMAX FL 693 M**

Version: STANDARD  
 US Code: 94045891  
 Type: TL  
 Tire Size: 560/60 R 22.5  
 LI/SS: 165 D/162 E



**Dimensions (U/M US Standard)**

Section Width (in): 21.4  
 Overall Diameter (in): 49.0  
 Static Loaded Radius (in): 21.6  
 Rolling Circumference (in): 148.3  
 SRI: 600  
 Rim Rec: AG 16.00  
 Rim Alt: 16.00 ; 17.00 ; AG 20.00

**LOAD CAPACITY TABLE (lbs)**

| mph / psi | 15   | 17   | 23   | 29    | 35    | 41    | 46    | 52    | 58    | 73    |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 3430 | 3850 | 4780 | 5430  | 6280  | 7120  | 7780  | 8530  | 9370  | 10470 |
| 40        | 3730 | 4190 | 5200 | 5920  | 6830  | 7750  | 8470  | 9280  | 10200 | 11350 |
| 30        | 4520 | 5070 | 6300 | 7160  | 8280  | 9390  | 10250 | 11240 | 12350 | 13750 |
| 25        | 5070 | 5690 | 7080 | 8050  | 9290  | 10550 | 11520 | 12620 | 13870 | 15440 |
| 15        | 5890 | 6610 | 8220 | 9350  | 10800 | 12260 | 13380 | 14670 | 16110 | 17940 |
| 5         | 6700 | 7530 | 9370 | 10650 | 12300 | 13950 | 15230 | 16710 | 18350 | 20440 |