

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD
 US Code 94046072
 Type TL
 Tire Size 420/80 R 46
 LI/SS 159 D/170 A2



Dimensions (U/M US Standard)

Section Width (in) 16.5
 Overall Diameter (in) 72.4
 Static Loaded Radius (in) 34.0
 Rolling Circumference (in) 221.2
 SRI 875
 Rim Rec W 13
 Rim Alt W 12

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
40	3580	4110	4720	5320	5940	6550	7080	7610	8970	9640
30	3760	4320	4960	5600	6240	6880	7440	7990	9420	10130
25	3920	4510	5170	5840	6500	7180	7760	8330	9830	10570
20	4120	4730	5430	6130	6830	7530	8150	8750	10330	11100
5	4930	5650	6490	7330	8170	9010	9740	10470	12300	13230
5 LT	4790	5510	6330	7140	7960	8770	9490	10200	12030	12930
5 HT	4120	4730	5430	6130	6830	7530	8150	8750	10330	11100