

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader
 Description FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

Pattern Name FL 630 SUPER

Version STANDARD
 US Code 94046096
 Type TL
 Tire Size 750/45 R 26.5
 LI/SS 170 D



Dimensions (U/M US Standard)
 Section Width (in) 29.7
 Overall Diameter (in) 53.1
 Static Loaded Radius (in) 23.9
 Rolling Circumference (in) 163.3
 SRI 650
 Rim Rec AG 24.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	3860	4400	4940	6140	6990	8070	9150	10000	10940	12040
40	4230	4830	5420	6750	7670	8860	10050	10980	12040	13230
30	5130	5850	6570	8170	9290	10720	12170	13290	14570	16000
25	5760	6580	7390	9180	10440	12060	13680	14940	16380	17990
15	6690	8580	10660	12120	14010	14010	15880	17350	19020	20900
5	7630	8700	9770	12150	13810	15960	18100	19760	21670	23810