

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: SPECIAL
 US Code: 94046737
 Type: TL
 Tire Size: 270/95 R 36
 LI/SS: 139 A8/B

Dimensions (U/M US Standard)
 Section Width (in): 10.8
 Overall Diameter (in): 56.2
 Static Loaded Radius (in): 26.2
 Rolling Circumference (in): 172
 SRI: 675
 Rim Rec: W 9
 Rim Alt: W 8 ; W 10



LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2090	2730	3330	3650	3860	4230	4610	4980	5350	-
25	2090	2730	3330	3650	3860	4230	4610	4980	5350	-
20	2250	2930	3570	3910	4140	4540	4950	5350	5740	-
5	2490	3140	3860	4590	5310	5470	6120	6760	7400	8040