

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version SPECIAL
 US Code 94047239
 Type TL
 Tire Size 320/85 R 34
 LI/SS 141 A8/B

Dimensions (U/M US Standard)

Section Width (in) 13.0
 Overall Diameter (in) 55.4
 Static Loaded Radius (in) 25.4
 Rolling Circumference (in) 168.5
 SRI 675
 Rim Rec W 11
 Rim Alt W 9 ; W 10



LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	17	23	29	35	41	46	52
30	2050	2390	3130	3810	4140	4430	4830	5220	5680
25	2050	2390	3130	3810	4140	4430	4830	5220	5680
20	2190	2560	3350	4080	4440	4750	5180	5600	6080
5 LT	2740	3210	4200	5100	5570	5940	6480	7010	7620
5 HT	2190	2560	3350	4080	4440	4750	5180	5600	6080