

## TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader

Description: RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

**Pattern Name**      **RIDEMAX FL 693 M**

Version: STANDARD  
 US Code: 94047277  
 Type: TL  
 Tire Size: 600/55 R 26.5  
 LI/SS: 165 D

Dimensions (U/M US Standard)

Section Width (in): 24.1  
 Overall Diameter (in): 52.5  
 Static Loaded Radius (in): 23.1  
 Rolling Circumference (in): 159.5  
 SRI: 625  
 Rim Rec: AG 20.00



**LOAD CAPACITY TABLE (lbs)**

| mph / psi | 15   | 17   | 23    | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 3840 | 4340 | 5280  | 6110  | 7030  | 7970  | 8590  | 9510  | 10340 |
| 40        | 4210 | 4770 | 5800  | 6700  | 7730  | 8750  | 9420  | 10450 | 11350 |
| 30        | 5090 | 5780 | 7010  | 8110  | 9350  | 10590 | 11420 | 12650 | 13750 |
| 25        | 5720 | 6490 | 7880  | 9120  | 10500 | 11890 | 12820 | 14210 | 15440 |
| 15        | 6650 | 7540 | 9160  | 10590 | 12210 | 13820 | 14900 | 16510 | 17940 |
| 5         | 7570 | 8590 | 10430 | 12060 | 13900 | 15740 | 16960 | 18800 | 20440 |