

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version SPECIAL
 US Code 94047543
 Type TL
 Tire Size 320/85 R 38
 LI/SS 143 A8/B

Dimensions (U/M US Standard)

Section Width (in) 12.6
 Overall Diameter (in) 59.4
 Static Loaded Radius (in) 27.6
 Rolling Circumference (in) 180.3
 SRI 725
 Rim Rec W 10
 Rim Alt W 9 ; W 11 ; DW 11



LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	17	23	29	35	41	46	52
30	2170	2520	3310	4030	4390	4700	5110	5530	6000
25	2170	2520	3310	4030	4390	4700	5110	5530	6000
20	2330	2710	3550	4320	4710	5030	5480	5930	6440
5 LT	2910	3390	4440	5400	5890	6290	6860	7420	8060
5 HT	2330	2710	3550	4320	4710	5030	5480	5930	6440