

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: SPECIAL
 US Code: 94047628
 Type: TL
 Tire Size: 270/95 R 48
 LI/SS: 144 A8/B



Dimensions (U/M US Standard)
 Section Width (in): 10.8
 Overall Diameter (in): 68.2
 Static Loaded Radius (in): 32.3
 Rolling Circumference (in): 210.7
 SRI: 825
 Rim Rec: W 9
 Rim Alt: W 8 ; W 10

LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2410	3150	3840	4200	4450	4880	5310	5740	6150	-
25	2410	3150	3840	4200	4450	4880	5310	5740	6150	-
20	2580	3370	4100	4500	4760	5220	5690	6150	6610	-
5	2880	3620	4450	5280	6120	6300	7040	7780	8520	9260