

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: SPECIAL
 US Code: 94047642
 Type: TL
 Tire Size: 270/95 R 54
 LI/SS: 146 A8/B

Dimensions (U/M US Standard)
 Section Width (in): 10.8
 Overall Diameter (in): 74.2
 Static Loaded Radius (in): 34.6
 Rolling Circumference (in): 228.9
 SRI: 925
 Rim Rec: W 9
 Rim Alt: W 8 ; W 10



LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2580	3370	4100	4500	4760	5220	5690	6150	6600	-
25	2580	3370	4100	4500	4760	5220	5690	6150	6600	-
20	2770	3620	4400	4820	5100	5600	6100	6590	7080	-
5	3080	3870	4760	5650	6550	6750	7540	8330	9130	9920