

## TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer  
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

**Pattern Name      AGRIMAX RT 955**

Version: SPECIAL  
 US Code: 94047703  
 Type: TL  
 Tire Size: 270/95 R 46  
 LI/SS: 143 A8/B



Dimensions (U/M US Standard)  
 Section Width (in): 10.8  
 Overall Diameter (in): 66.3  
 Static Loaded Radius (in): 30.9  
 Rolling Circumference (in): 198.8  
 SRI: 825  
 Rim Rec: W 9  
 Rim Alt: W 8 ; W 10

**LOAD CAPACITY TABLE (lbs)**

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2470	3190	3850	4210	4510	4930	5360	5710	6000	-
25	2470	3190	3850	4210	4510	4930	5360	5710	6000	-
20	2650	3420	4120	4510	4830	5280	5730	6120	6440	-
5	3410	4410	5310	5820	6230	6810	7400	7890	8300	9020