

TECHNICAL SPECIFICATION

Applications Telehandler / Compact Loader / Backhoe Loader

Description MULTIMAX MP 522 is the BKT multi-purpose tire developed for manifold agro-industrial applications. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders. Stability and high load capacity are its strengths as well as outstanding puncture resistance. Multimax MP 522 is the right response for all agro-industrial heavy-duty needs.

Pattern Name **MULTIMAX MP 522**

Version STANDARD
US Code 94048793
Type TL
Tire Size 340/80 R 18 IND
LI/SS 143 A8/B

Dimensions (U/M US Standard)

Section Width (in) 13.5
Overall Diameter (in) 39.4
Static Loaded Radius (in) 18.0
Rolling Circumference (in) 118.2
SRI 475
Rim Rec 11 ; 11 SDC ; W 11
Rim Alt W 10 ; 12 ; 12 SDC
ECE E4-106R-002654



LOAD CAPACITY TABLE (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	2890	3430	3910	4450	4990	5360	6010	-	-
25	2890	3430	3910	4450	4990	5360	6010	-	-
20	3100	3670	4190	4770	5350	5730	6440	-	-
15	3210	3800	4340	4940	5540	5940	6670	-	-
5 Cyc.	3530	4330	5100	5860	6680	7260	8210	8660	9020
Static	5400	6640	7810	8990	10230	11130	12590	13270	13820