

TECHNICAL SPECIFICATION

Applications: Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description: AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504
 Version STANDARD
 Type TL
 Tire Size 9.0/70 - 16
 PR 10



Dimensions (U/M US Standard)
 Section Width (in) 8.7
 Overall Diameter (in) 29.9
 Static Loaded Radius (in) 14.0
 Rolling Circumference (in) 90
 Rim Rec W 7

Applications: Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description: AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

LOAD CAPACITY TABLE (lbs)

mph / psi	64
5 FR	4200
15 FR	3570
20 FR	3360
25 FR	3000
5 DW	2930
15 DW	2490
20 DW	2350
25 DW	2090

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%