

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader
 Description FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

Pattern Name FL 630 SUPER

Version HD
 US Code 94048946
 Type TL
 Tire Size 600/55 R 26.5
 LI/SS 177 D



Dimensions (U/M US Standard)
 Section Width (in) 24.1
 Overall Diameter (in) 52.5
 Static Loaded Radius (in) 23.8
 Rolling Circumference (in) 161.6
 SRI 625
 Rim Rec AG 20.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58	73	87
40	4020	4990	5960	7240	8380	9660	10950	11750	13040	14330	15130	16090
30	4870	6040	7210	8770	10130	11690	13250	14220	15780	17340	18310	19480
25	5480	6790	8100	9850	11390	13140	14890	15980	17740	19490	20580	21890
20	6080	7540	8990	10950	12640	14580	16530	17750	19700	21640	22850	24300
15	6360	7890	9410	11450	12320	15270	17290	18570	20600	22640	23910	25430
5	7240	8980	10720	13040	15070	17380	19710	21150	23470	25780	27240	28970