

## TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer  
 Description: AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

**Pattern Name      AGRIMAX RT 855**

Version: STANDARD  
 US Code: 94049332  
 Type: TL  
 Tire Size: 250/85 R 22  
 LI/SS: 113 A8/B



Dimensions (U/M US Standard)  
 Section Width (in): 9.9  
 Overall Diameter (in): 38.8  
 Static Loaded Radius (in): 17.8  
 Rolling Circumference (in): 116.7  
 SRI: 475  
 Rim Rec: W 8  
 Rim Alt: W 7

**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23	29	35
30	1200	1380	1580	1770	1980	2180	2360	2540
25	1200	1380	1580	1770	1980	2180	2360	2540
20	1290	1480	1700	1910	2130	2350	2540	2720
5 LT	1610	1840	2120	2390	2670	2930	3170	3410
5 HT	1290	1480	1700	1910	2130	2350	2540	2720