

TECHNICAL SPECIFICATION

Applications: Trailer / Implement Machinery / Compact Dumper
 Description: FLOTATION TR 675 is best suited for soil tillage operations and transport. It fits trailers, compact dumpers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction remaining gentle on the ground to prevent crop damages.

Pattern Name **FLOTATION TR 675**

Version: DUAL BEAD
 US Code: 94050147
 Type: TL
 Tire Size: 500/60 - 22.5
 PR: 20



Dimensions (U/M US Standard)

Section Width (in): 19.7
 Overall Diameter (in): 46.5
 Static Loaded Radius (in): 21.0
 Rolling Circumference (in): 138
 Rim Rec: AG 16.00
 Rim Alt: 15.00 ; 17.00
 ECE: E11-106R-004395

LOAD CAPACITY TABLE (lbs)

mph / psi	54	55	58
5 FR	16370	16630	17280
10 FR	14740	14970	15550
20 FR	13090	13300	13820
25 FR	11690	11880	12350
30 FR	10530	10690	11020
5 DW	11580	11770	11960
10 DW	10430	10590	10770
20 DW	9270	9420	9570
25 DW	8280	8410	8540
30 DW	7450	7570	7610

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%