

**TECHNICAL SPECIFICATION**

Applications                      Trailer  
 Description                      CON TRAILER is a trailer tire particularly suitable for port applications. It is the ideal tire for on-and-off-the-road applications. Its robust construction results in high load capacity, whereas its extra-deep tread allows for a better mileage.

**Pattern Name                      CON TRAILER**

Version                              PORT INDUSTRIAL  
 US Code                            94050369  
 Type                                 TT  
 Tire Size                          10.00 - 20  
 PR                                    18



Dimensions (U/M US Standard)  
 Section Width (in)              11.3  
 Overall Diameter (in)          42.5  
 Rim Rec                            7.5  
 Rim Alt                             7.0 ; 8.0

**LOAD CAPACITY TABLE (lbs)**

mph / psi	-	-
-	-	-
-	-	-

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..