

TECHNICAL SPECIFICATION

Applications Telehandler / Compact Loader / Backhoe Loader

Description MULTIMAX MP 522 is the BKT multi-purpose tire developed for manifold agro-industrial applications. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders. Stability and high load capacity are its strengths as well as outstanding puncture resistance. Multimax MP 522 is the right response for all agro-industrial heavy-duty needs.

Pattern Name **MULTIMAX MP 522**

Version STANDARD
US Code 94051403
Type TL
Tire Size 400/70 R 24 IND
LI/SS 152 A8/B



Dimensions (U/M US Standard)

Section Width (in) 15.9
Overall Diameter (in) 46.1
Static Loaded Radius (in) 21.0
Rolling Circumference (in) 138.9
SRI 575
Rim Rec 13
Rim Alt DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L
ECE E11-106R-002964

LOAD CAPACITY TABLE (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	3760	4460	5090	5800	6500	6970	7830	-	-
25	3760	4460	5090	5800	6500	6970	7830	-	-
20	4020	4780	5450	6210	6960	7460	8380	-	-
15	4180	4960	5650	6440	7220	7750	8700	-	-
5 Cyc.	4590	5640	6640	7640	8700	9460	10690	11280	11740
Static	7020	8640	10170	11710	13330	14490	16390	17280	18000