

**TECHNICAL SPECIFICATION**

Applications                    Trencher / Orchard Harvester / Implement Machinery  
 Description                    TR 319 is a tire for implement machinery, orchard harvesters and trenchers in lawn and garden as well as soil tillage applications. Featuring a large contact area providing best traction, TR 319 is very suitable for applications on wet and dry surfaces.

**Pattern Name**                **TR 319**  
 Version                         STANDARD  
 US Code                        94051601  
 Type                             TL  
 Tire Size                        29 X 12.50 - 15  
 LI/SS                            98 B  
 PR                                6



Dimensions (U/M US Standard)  
 Section Width (in)            12.3  
 Overall Diameter (in)        29.7  
 Static Loaded Radius (in)    14.2  
 Rolling Circumference (in)   89.1  
 Rim Rec                         10 LB

**LOAD CAPACITY TABLE (lbs)**

mph / psi	30
30	1650

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.  
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..