

## TECHNICAL SPECIFICATION

**Applications** Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

**Description** AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

**Pattern Name AS 504**

Version STANDARD  
 US Code 94052011  
 Type TL  
 Tire Size 5.00 - 15  
 PR 6



**Dimensions (U/M US Standard)**

Section Width (in) 5.5  
 Overall Diameter (in) 25.9  
 Static Loaded Radius (in) 12.1  
 Rolling Circumference (in) 77  
 SRI 310  
 Rim Rec 3.50 D  
 Rim Alt 3.00 D ; 4.00 E ; 4 J  
 ECE E4-106R-001950

**LOAD CAPACITY TABLE (lbs)**

mph / psi	51
5 FR	1730
15 FR	1470
20 FR	1380
25 FR	1230
5 DW	1190
15 DW	1010
20 DW	950
25 DW	850

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%