

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name **AS 504**

Version STANDARD

Type TL

Tire Size 5.00 - 15

PR 6



Dimensions (U/M US Standard)

Section Width (in) 5.5

Overall Diameter (in) 25.9

Static Loaded Radius (in) 12.1

Rolling Circumference (in) 77

SRI 310

Rim Rec 3.50 D

Rim Alt 3.00 D ; 4.00 E ; 4 J

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

LOAD CAPACITY TABLE (lbs)

mph / psi	51
5 FR	1730
15 FR	1470
20 FR	1380
25 FR	1230
5 DW	1190
15 DW	1010
20 DW	950
25 DW	850

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%