

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504

Version STANDARD
 US Code 94052011
 Type TL
 Tire Size 5.00 - 15
 PR 6

Dimensions (U/M US Standard)

Section Width (in) 5.5
 Overall Diameter (in) 25.9
 Static Loaded Radius (in) 12.1
 Rolling Circumference (in) 77
 SRI 310
 Rim Rec 3.50 D
 Rim Alt 3.00 D ; 4.00 E ; 4 J



LOAD CAPACITY TABLE (lbs)

mph / psi	51
5 FR	1730
15 FR	1470
20 FR	1380
25 FR	1230
5 DW	1190
15 DW	1010
20 DW	950
25 DW	850

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%