

TECHNICAL SPECIFICATION

Applications: Trailer / Hay Harvester / Baler
 Description: FLOTATION 648 T is particularly suitable for field and road transport as well as for hay harvesting. Its tread design allows for carrying very high loads at low pressure and ensures outstanding self-cleaning properties. In line with BKT's commitment to provide products supporting the farming business, FLOTATION 648 T maximizes your yield and takes care of the land.

Pattern Name **FLOTATION 648 T**

Version: STANDARD
 US Code: 94052066
 Type: TL
 Tire Size: 550/45 - 22.5
 PR: 16



Dimensions (U/M US Standard)
 Section Width (in): 21.7
 Overall Diameter (in): 42.1
 Static Loaded Radius (in): 18.7
 Rolling Circumference (in): 126.1
 Rim Rec: AG 16.00

LOAD CAPACITY TABLE (lbs)

mph / psi	35	38	41
5 FR	12350	12930	13500
10 FR	11110	11640	12160
20 FR	9880	10350	10800
25 FR	8820	9240	9640
30 FR	7940	8310	8820
5 DW	8670	9090	9490
10 DW	7800	8180	8540
20 DW	6930	7270	7590
25 DW	6190	6490	6780
30 DW	5580	5840	6170

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%