

TECHNICAL SPECIFICATION

Applications Telehandler / Compact Loader / Backhoe Loader

Description MULTIMAX MP 522 is the BKT multi-purpose tire developed for manifold agro-industrial applications. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders. Stability and high load capacity are its strengths as well as outstanding puncture resistance. Multimax MP 522 is the right response for all agro-industrial heavy-duty needs.

Pattern Name **MULTIMAX MP 522**

Version STANDARD
US Code 94052240
Type TL
Tire Size 440/80 R 28 IND
LI/SS 156 A8/B



Dimensions (U/M US Standard)

Section Width (in) 17.4
Overall Diameter (in) 55.7
Static Loaded Radius (in) 25.3
Rolling Circumference (in) 168.4
SRI 675
Rim Rec DW 14 L
Rim Alt DW 13 ; DW 13 L ; DW 15 L
ECE E11-106R-002968

LOAD CAPACITY TABLE (lbs)

mph / psi	23	29	32	35	38	41	44	46	49	52
30	5070	6010	6480	6940	7410	7880	8360	8820	-	-
25	5070	6010	6480	6940	7410	7880	8360	8820	-	-
20	5470	6460	6960	7450	7950	8440	8940	9440	-	-
15	5670	6700	7210	7730	8240	8750	9270	9790	-	-
5 Cyc.	6260	7650	8360	9050	9740	10440	11130	11840	12530	13230
Static	9610	11750	12810	13880	14950	16020	17080	18140	19210	20280