

TECHNICAL SPECIFICATION

Applications Telehandler / Compact Loader / Backhoe Loader

Description MULTIMAX MP 522 is the BKT multi-purpose tire developed for manifold agro-industrial applications. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders. Stability and high load capacity are its strengths as well as outstanding puncture resistance. Multimax MP 522 is the right response for all agro-industrial heavy-duty needs.

Pattern Name **MULTIMAX MP 522**

Version STANDARD
US Code 94052257
Type TL
Tire Size 440/80 R 24 IND
LI/SS 161 A8/B



Dimensions (U/M US Standard)

Section Width (in) 17.4
Overall Diameter (in) 51.7
Static Loaded Radius (in) 23.1
Rolling Circumference (in) 155.7
SRI 625
Rim Rec DW 14 L
Rim Alt DW 13 ; DW 13 L ; DW 15 L
ECE E11-106R-002966

LOAD CAPACITY TABLE (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	4890	5820	6640	7550	8470	9080	10200	-	-
25	4890	5820	6640	7550	8470	9080	10200	-	-
20	5250	6230	7100	8080	9060	9720	10910	-	-
15	5430	6460	7360	8380	9400	10090	11320	-	-
5 Cyc.	5970	7350	8650	9950	11330	12320	13930	14690	15300
Static	9150	11260	13260	15260	17360	18890	21350	22520	23460