

TECHNICAL SPECIFICATION

Applications Telehandler / Compact Loader / Backhoe Loader

Description MULTIMAX MP 522 is the BKT multi-purpose tire developed for manifold agro-industrial applications. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders. Stability and high load capacity are its strengths as well as outstanding puncture resistance. Multimax MP 522 is the right response for all agro-industrial heavy-duty needs.

Pattern Name **MULTIMAX MP 522**

Version STANDARD
US Code 94052264
Type TL
Tire Size 540/70 R 24 IND
LI/SS 168 A8/B



Dimensions (U/M US Standard)

Section Width (in) 20.9
Overall Diameter (in) 53.8
Static Loaded Radius (in) 24.1
Rolling Circumference (in) 162.7
SRI 650
Rim Rec DW 16 L
Rim Alt DW 18 L
ECE E11-106R-002967

LOAD CAPACITY TABLE (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	5930	7040	8020	9140	10250	10990	12350	-	-
25	5930	7040	8020	9140	10250	10990	12350	-	-
20	6350	7540	8600	9790	10980	11770	13220	-	-
15	6590	7830	8920	10150	11390	12210	13710	-	-
5 Cyc.	7230	8900	10470	12040	13710	14910	16850	17780	18520
Static	11080	13630	16050	18460	21020	22860	25850	27260	28390