

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor
 Description: AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name AGRIMAX RT 657

Version: STANDARD
 Type: TL
 Tire Size: 420/65 R 28
 LI/SS: 135 D/138 A8

Dimensions (U/M International standard)

Section Width (mm): 418
 Overall Diameter (mm): 1257
 Static Loaded Radius (mm): 584
 Rolling Circumference (mm): 3824
 SRI: 600
 Rim Rec: W 13
 Rim Alt: W 12 ; W 11



LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1025	1180	1355	1530	1705	1875	2030	2180
50	1080	1240	1420	1605	1790	1970	2130	2290
40	1110	1275	1465	1655	1845	2030	2195	2360
25	1215	1400	1605	1810	2020	2225	2405	2585
10	1540	1770	2030	2290	2555	2815	3045	3270