

## TECHNICAL SPECIFICATION

**Applications** Vineyard Harvester / Tractor / Sprayer

**Description** AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

**Pattern Name**      **AGRIMAX RT 855**

Version                      STANDARD  
 US Code                    94052691  
 Type                         TL  
 Tire Size                  320/85 R 36  
 LI/SS                        147 D/150 A8



**Dimensions (U/M US Standard)**

Section Width (in)      13.0  
 Overall Diameter (in)    57.4  
 Static Loaded Radius (in) 26.5  
 Rolling Circumference (in) 173.4  
 SRI                         700  
 Rim Rec                    W 11  
 Rim Alt                    W 9 ; W 10

**LOAD CAPACITY TABLE (lbs)**

| mph / psi | 12   | 15   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 64   |
|-----------|------|------|------|------|------|------|------|------|------|------|------|
| 45        | 2560 | 2930 | 3310 | 3990 | 4430 | 4670 | 5110 | 5540 | 5920 | 6230 | 6780 |
| 30        | 2690 | 3090 | 3470 | 4200 | 4650 | 4920 | 5380 | 5830 | 6230 | 6550 | 7120 |
| 25        | 2800 | 3210 | 3630 | 4380 | 4850 | 5130 | 5600 | 6070 | 6490 | 6820 | 7390 |
| 20        | 2940 | 3370 | 3800 | 4590 | 5090 | 5380 | 5870 | 6380 | 6810 | 7160 | 7800 |
| 5 LT      | 3430 | 3940 | 4430 | 5360 | 5940 | 6270 | 6860 | 7440 | 7950 | 8360 | 9090 |
| 5 HT      | 2940 | 3370 | 3800 | 4590 | 5090 | 5380 | 5870 | 6380 | 6810 | 7160 | 7800 |