

TECHNICAL SPECIFICATION

Applications Telehandler / Compact Loader / Backhoe Loader

Description MULTIMAX MP 522 is the BKT multi-purpose tire developed for manifold agro-industrial applications. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders. Stability and high load capacity are its strengths as well as outstanding puncture resistance. Multimax MP 522 is the right response for all agro-industrial heavy-duty needs.

Pattern Name **MULTIMAX MP 522**

Version STANDARD
US Code 94052707
Type TL
Tire Size 480/80 R 26 IND
LI/SS 160 A8/B



Dimensions (U/M US Standard)

Section Width (in) 18.9
Overall Diameter (in) 56.2
Static Loaded Radius (in) 25.1
Rolling Circumference (in) 168.8
SRI 675
Rim Rec DW 15 L
Rim Alt DW 16 L
ECE E11-106R-002970

LOAD CAPACITY TABLE (lbs)

mph / psi	23	29	32	35	38	41	44	46	49	52
30	5750	6750	7340	7840	8330	8830	9420	9920	-	-
25	5750	6750	7340	7840	8330	8830	9420	9920	-	-
20	6160	7220	7860	8390	8920	9460	10090	10610	-	-
15	6390	7500	8160	8710	9260	9810	10470	11010	-	-
5 Cyc.	7000	8630	9380	10120	11010	11760	12500	13390	14140	14880
Static	10720	13240	14380	15520	16890	18030	19170	20530	21680	22820