

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader
Description FL 630 ULTRA is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering. The particular tread design ensures excellent grip on any kind of terrain in addition to enhanced self-cleaning features.

Pattern Name **FL 630 ULTRA**

Version STANDARD
US Code 94052790
Type TL
Tire Size 560/45 R 22.5
LI/SS 152 D/163 A8



Dimensions (U/M US Standard)
Section Width (in) 21.4
Overall Diameter (in) 42.4
Static Loaded Radius (in) 19.3
Rolling Circumference (in) 129.5
SRI 525
Rim Rec AG 16.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	2290	2610	2930	3640	4140	4780	5420	5930	6490	7130
40	2510	2870	3220	4000	4540	5250	5950	6500	7130	7830
30	3040	3470	3890	4840	5500	6360	7210	7870	8630	9480
25	3440	3920	4410	5490	6240	7210	8170	8930	9790	10750
20	3790	4320	4850	6040	6870	7930	8990	9820	10770	11830
15	3970	4530	5080	6320	7180	8290	9400	10270	11260	12370
5	4510	5150	5780	7190	8180	9450	10710	11690	12820	14090